



# ULTRA

DEXRON III

## AUTOMATIC TRANSMISSION FLUID

### DESCRIPTION

It is formulated with selected high quality refined mineral base oils and enriched with advanced technology additives. Meets performance requirements of various on and off-road vehicles which specify the Dexron III, IID, or II, Allison C-4, Ford Mercon, CAT TO-2 are recommended.

### APPLICATION

- It is designed for most Power transmission and hydraulic systems to include passenger car and truck automatic transmission.
- It can be used in industrial, agricultural, and off -highway applications where it requires Dex III.

### BENEFITS

- Longer transmission, torque converter, hydraulic system life.
- Excellent low temperature fluidity. Excellent resistance to oxidation and high thermal stability.
- Less maintenance, keeps downtime to a minimum.
- Provides good wear protection and durability of friction characteristics.

### SPECIFICATIONS

Dexron III, Dexron IID, Ford MERCON, Allison C-4, CAT TO-2 ; Voith G607;Sperry Vickers; Denison: Sundstrand

### TYPICAL PROPERTIES

Properties	Results	Method
ATF TYPE	Dexron III	-----
Density @ 15° C, g/ml	0.866	ASTM D-1298
Flash Point, COC, °C	190	ASTM D-92
Pour Point, °C	-42	ASTM D-97
Viscosity @ 40°C, cSt	37	ASTM D-445
Viscosity @ 100°C, cSt	7.8	ASTM D-445
Viscosity Index	188	ASTM D-2270

